Poolstar
Source d'innovation

For pools up to 110m³ | Operates down to -10°c | 5 versions available

POOLEX
SUIVEZ L'EXPERT

JETLINE SELECTION Fi

JETLINE SELECTION Fi

Full inverter technology for everyone

- **Full Inverter** Technology
  Compressor Technology
  + Variable Speed Fan
- Ultra silent
- Automatic defrosting
- Titanium Twisted Exchanger Tech

	75	95	125	155	210
Pool volume	30-45m3	40-50m3	45-65m3	65-80m3	80-110m3
cop air 26°C /water 26°C	6.2~13.6	6.3~14	6.2~16.4	6.1~16.3	6.2~16.5
Noise at 10m(db(a))	19~29	19~30	21~31	23~34	23~35

HEAT PUMP GUARANTEED 2 YEARS

COMPRESSOR GUARANTEED 5 YEARS

TITANIUM COIL GUARANTEED AGAINST CORROSION 15 YEARS

SYSTÈME ANTIGEL BREVETÉ

ABS MATERIAL DURABLE

SILENT EFFICIENCY

NEW R32 OZONE FRIENDLY

COMPRESSOR MITSUBISHI INSIDE

Wifi intégré

TRAITEMENT SEL

WWW.POOLSTAR.FR

Poolstar
Source d'innovation

POOLEX
SUIVEZ L'EXPERT

JETLINE SELECTION Fi

For pools up to 110m³ | Operates down to -10°c | 5 versions available

JETLINE SELECTION Fi		75	95	125	155	210
Pool volume		30 to 45m³	40 to 50m³	45 to 65m³	65 to 80m³	80 to 110m³
	Reference : PC-JLS	075N	095N	125N	155N	210N
Air 26°C Water 26°C Hygro 80%	**Max. power output(kW)**	**7,1**	**9,5**	**11,9**	**15,3**	**20,1**
	Min. power output (kW)	**2,04**	**2,3**	**2,35**	**2,5**	**2,77**
	Power consumption (kW)	**1,15**	**1,51**	**1,92**	**2,51**	**3,24**
	COP	**6.2 ~ 13.6**	**6.3 ~ 14**	**6.2 ~ 16.4**	**6.1 ~ 16.3**	**6.2 ~ 16.5**
Air 15°C Water 26°C Hygro 70%	Max. power output (kW)	5,4	6,7	8,7	10,9	14,6
	Min. power output (kW)	1,4	1,5	1,7	1,9	2,15
	Power consumption (kW)	1,15	1,49	1,89	2,37	3,17
	COP	4.7 ~ 6.5	4.5 ~ 6.6	4.6 ~ 7.8	4.6 ~ 7.7	4.6 ~ 7.9
Electricity supply		Mono 230V / 50Hz				
Heating temperature range		15°C / 40°C				
Operating range		-7°C / 43°C				
Max. power (kW)		1.38	1.83	2.62	2.9	4.2
Flow (m³/h)		2~4	3~4	4~6	5~7	7~9
Refrigerant		R32				
Dimensions (mm)		824x334x656			907x334x656	1104x354x756
Packaging dimensions (mm)		886x404x778			969x404x778	1166x424x878
Noise level at 1 m (dB(A)) Inverter		37~50	37~51	38~52	40~54	41~55
Noise level at 10 m (dB(A)) Inverter		**19~29**	**19~30**	**21~31**	**23~34**	**23~35**
Compressor type		Rotatif double				
Compressor brand		**Mitsubishi**				
Heat exchanger		Twisted Tech© Titane				
Function		**Auto / Boost / Eco / Heating / Cooling**				

STANDARD E.U.
CERTIFIÉ T.Ü.V.

Informations données à titre indicatif et susceptibles d'être modifiées sans préavis

In its quest to deliver best performance to its clients, Poolex has developed a Jetline Selection heat pump equipped with Full Inverter Technology.

With an ultra efficient compressor and its variable speed blower, as well as a double coil titanium heat exchanger, this pump features a COP above 16 in 26/26* conditions.

Its LCD control pannel can be managed remotely with a 10m extension. The Jetline Selection Full Inverter can operate down to -10°C thanks to its high quality elements.

The Jetline Selection Full Inverter comprises of three operating modes:

- **Eco Booster** (Full Inverter) mode enabling it to adjust its power capacity and consumption on demand. Maximum power capacity at the beginning of the season to quickly heat up the swimming pool and then lower consumption to maintain pool temperature.
- **Eco Silence mode, economical and ultra silent thanks to a low blower rotation.**
- **Cruise** (ON/OFF) mode with continuous even performance.

The POOLEX Advantage: All accessories included

Delivered on wooden pallet

Isothermal winter storage cover

Anti-vibration support kit

Ø 50mm 1'' ½ Connectors PVC

Wired control extension (10m)

Condensation drainage pipe

Maintenance kit Including multi-language usermanual

Poolstar
Source d'innovation

For more information
on our products and services
www.poolstar.fr

REVENDEUR AGRÉÉ

Edition Septembre 2019